

PRINTER **TRE** full

index

Main Page

Technical Features



PRINTER **TRE** full

Magnetic card reader embedded tracks I - II - III

Digitax
AUTOMOTIVE ELECTRONICS

PRINTER **TRE** full



FRONT VIEW



SIDE VIEW



BACK VIEW



UPPER VIEW

Technical Features

INTRODUCTION

The **PRINTER TRE** has a wide range of uses in addition to the standard printing ones:

High printing speed: 30 – 35 mm/sec.

Power Supply 9 – 16V.

Easy paper change (Autoload).

Paper and sensor.

ESC/POSTM emulation.

Standard international characters font.

Standard line printing with autofeed.

Two dimension font scaling.

Print Density.

Online device checking.

Graphic image mode for bitmap printings.

Load Logos into printer memory (average logo size 3 Kb each).

Available memory for logo's storage (30 Kb).

Print selected logo command.

RS232 or TTL serial interface (2400-19200bps).

Dimensions (in millimeters)

Width	Height	Depth
85	51,5	90

APPLICATION NOTES

Temperature range (operation):

0° C to + 50° C

Temperature range (storage):

-25° C to + 70° C

Humidity range (operation):

10% to 95% without condensation

Humidity range (storage):

Up to 95% without condensation

To prevent stepper motor thermal overheating, it is required to respect a maximum on/off printing ratio (duty cycle) of 80-90%.

The printer may not print if power supply voltage is out of operating range 9 – 16V.

GENERAL FEATURES

Resolution

200 dpi (8dots/mm)

Maximum Print Speed

450 Dot Lines /s

Horizontal Dot Pitch

0.125 mm

Vertical Dot Pitch

0.125 mm

Printing Method

Direct Thermal, Line Dot Printing

Total Number of Dots / Line

384

Paper

Standard Thermal Paper 57 mm x 30 mm diameter, printable area: 48 mm

Interface

RS232 9600 Baud N81 or TTL

Magnetic card reader embedded tracks I - II - III (Option)

PRINTER TRE full



HIGH PERFORMANCE SPEED GRAPHIC PRINTER

The Receipt Printer Mod. "TRE" from Digitax can achieve near optimal speed graphic printing, thanks to the advanced architecture and structured graphic data management. Bitmap Logos are kept inside the printer memory, thus allowing a fast retrieval and direct paper exposition, without the need to decode and plot line by line.

A powerful and yet simple compression protocol enhances both the printer speed and the transfer rate during the logo's loading phase. And all of this with no need to sacrifice the printing quality, since the exposition time stays untouched. Besides, the relevant number of Bitmaps carried by the printer allows the user to program scheduled printings, conditioning logo's appearance by date and time.

Really we can say that it is now possible to reach outstanding performances with no system overhead, by means of the Digitax Receipt Printer Mod. "TRE".

PRINTER TRE full

Magnetic card reader embedded tracks I - II - III



Digitax Italy Headquarter

Via dell'Industria 16 - 62017 Porto Recanati (MC) - ITALY

Phone +39 071 7590984 r.a. - Fax +39 071 9797405

E-mail info@digitax.com - Web www.digitax.com

Digitax España

C/Mallorca, 114-116
Entresuelo 1ero - A
08029 - Barcelona
SPAIN
Phone +34 934 863 835
Fax +34 934 863 836
Web: www.digitax-es.com
E-mail: info@digitax-es.com

Digitax Electronincs U.K.

Smokehouse, 31
Tanners Bank North Shields
Tyne & Wear NE 30 1 JH
ENGLAND
Phone +44 (0191) 296 1294
Fax +44 (0191) 257 8438
Web: www.digitax.net
E-mail: digitaxuk@aol.com

Digitax Deutschland

Taxitech Handelsges. mbh
Sommerkamp 31a - 22335
Hamburg
GERMANY
Phone +49 40 555 05540
Fax +49 40 555 05530
Web: www.digitax-de.com
E-mail: digitax@taxitech.de

Digitax Nederland B.V.

Postbus 84112
3009 CC ROTTERDAM
HOLLAND
Phone +31 10 4512121
Fax : +31 10 4500453
E-mail: h.wittenberg@planet.nl
E-mail: info@digitax.nu

Digitax CO. Mauritius

P.O. box 775
Bel Village
MAURITIUS
Phone +230 234 4533/4936
Fax +230 234 5866
Web: www.mtl-co.net
E-mail: mtlts@intnet.mu