

# X-One

ANDROID



CAN BUS Interface



GLONASS/GPS/BeiDou



USB Interface



DIGITAX SDK



Dedicated CPU for  
Automotive Intensive  
Task Processor



System on Chip Module



Cat.6 LTE Module



Serial Port Interface



WLAN 2.4G, 802.11b/g/n  
BT 2.1 + EDR/3.0/4.1 LE



Android 9.x



Powerful Multimedia  
Function



The new X-One Android device is industrial grade and automotive certificate mobile data terminal.

## **DUAL CPU**

Primary CPU:

Qualcom Quad Cortex 1.4GHz processor with Adreno 304 GPU, OpenGL ES 3.0, OpenCL, DirectX, content security and QDSP6 DSP inside, allows this Device to supply a remarkable flexibility and efficiency in computing power, together with reduced power consumption.

Secondary CPU:

AITP (Automotive Intensive Task Processor) dedicated to the necessary functionalities in the automotive field, like power management, Safe Shutdown, Wheel Pulses Odometer, Distance and Speed calculation, Wake-Up on Ring, Over-the-Air services for software and firmware updates. The AITP is OTA programmable for remote automatic firmware and tariff upgrade, and is always powered ON; it can turn-ON and OFF the Device and its peripherals.

## **IDEAL FOR FLEET MANAGEMENT**

The Device represents the state-of-the-art device for security and fleets management, an ALL-IN-ONE industrial grade and automotive compliant, powerful and compact solution.

Its 4G LTE modem allows very reliable communication with operating headquarters.

The vehicle is located by the high performance GPS/GLONASS/BeiDo receiver.

## **CUSTOMIZABLE USER INTERFACE**

The 7 inches 16:9 clear readable TFT Displays with HD 1024x800 @60fp resolution allow to develop versatile and high accessible applications, thanks also to the integrated TouchScreen controller, and to the 6 keys with LEDs available.

Hardware Keys avoid consumption and damage of Touch Screen for heavily used operations.

to choose The ambient light sensor allows an optimal brightness of the display in any environmental light.

The power key is a Smart Power Button, completely programmable and used to perform several important tasks.

Can be also disabled or programmed to trigger Ghost Mode (fake shutdown).

## **STEALTH MODE**

Stealth mode is a special operating mode in which the system is working but the display and audio is OFF.

This feature can be useful in several situations:

Driver Control: System has also the wake up on ring feature, so at the central it is possible to remotely turn-ON the device (also in stealth mode so nobody can see that it is starting) in order to check vehicle position, internal audio listening and other data.

Ghost Mode: It is possible to set the device so that after pressing the shut down but on the system goes on stealth mode instead of turning OFF. This feature is useful if you want the device to remain always ON (it turns OFF only the display, reducing power consumption) or in an alarm situation.

Alarm managing: If system is OFF and alarm but on is pressed the system can be started in stealth mode, so nobody can see that the system starts. On this special start the system can be programmed for example to send an alarm message to the central, GPS position or also screenshots or audio..

## **HIGH AVAILABILITY**

The Device has been designed for professional automotive application, it is fully automotive certified, can withstand glitches at car engine start, over voltage up to 32V and immunity to ESD and EMC interferences

The AITP processor gives time to user applications and Android O.S. to close gracefully and safely in case of sudden disconnection of the Main Power.

## **INPUTS AND OUTPUTS**

The Device supplies a wide range of communication channels with the external environment: Hi-Speed USB 2.0 Host, one USB Device and up to 7 RS232 and RS485 Serial Ports.

The special programmable digital inputs and outputs allow to control devices and read signals coming from generic external equipment's.



# MAIN FEATURES



Display
Viewing area 7" diagonal
Aspect Ratio 16:9
WVGA 1024x800 Resolution
Colour TFT LED Display
Display clearly viewable with 500 cd/m2
Ambient Light Sensor with Automatic Regulation

Touchscreen
Capacitive Touch screen.
Extended Temperature Range

CPUs
Fanless Device with Primary CPU Qualcomm Quad Cortex 1.4GHz. Adreno 304 GPU: OpenGL ES 3.02, OpenCL3, DirectX, content security, and decreased power consumption4
Secondary M16 CPU for Automotive Intensive Tasks

Ram Memory
+1GB LPDDR3

Storage Solid State Hard Disk Memory
8GB EMMC

External SD
Up to 256 GB for external storage

Communication Modem
LTE Cat 4
GSM / GPRS Class 12 HSUPA Modem with 150Mbit/s downlink and 50Mbit/s uplink data rates based on LTE network (max)
Warm reset and cold reset (dedicated electronic circuit) available through API calls
2 Sim Card slots.

GPS Receiver
Multi-constellation GNSS receiver available for applications requiring fast and accurate fixes in any environment.

Antennas
Internal GPS-WiFi-BT-LTE or External GPS-WiFi-BT-LTE Rugged Combo antenna (option)

USB Ports
2 USB 2.0 Host (with USB Support for Mouse and Keyboard) Hi-Speed
1 USB 2.0 / OTG Host / Device

Serial Ports
1 External Full Modem RS232 Port
2 External TX/RX RS232 / RS485 Port
4 External RS232 Serial Ports (option)

I/O ports connection
3 Digital Inputs
3 + 5 Power Output Ports
Dedicated Ignition input
2 Analog Ports input
External Speakers output
External Microphone input

Alarm and Security
Panic Button input / Emergency Switch input
Stealth Mode Controller (system ON display, audio and lightings off)

Hardware Keys
6 Lighted and Software programmable Hardware Buttons

Power on key
1 Smart Power On/Off button

Multimedia
Audio: MP3, AAC+,eAAC, AMR-NB, -WB, G.711, WMA 9/10 Pro
Video: Encode:30fps 720P (H.264), 30fps WVGA (MPEG-4/VP8)
Decode:30fps 1080P (H.264/MPEG-4/VP8/H.265 DivX4/5/6), 30fps WVGA (H.263)
Internal and external Speaker and Microphone
Supports wave speaker volume control

API provided
Soft/Hard Reset
Soft Reset available through HW switch
Soft Reset available through API calls

Connectivity
Ethernet: 10/100 Mbps LAN Controller
Wi-Fi Connection 2.4G/5.8G, 802.11 a/b/g/n
Bluetooth class 2 BT2.1+EDR/3.0/4.1 LE

Operating System
Android 6.0/7.1
Development Tools
Adb/Android Studio IDE with USB debugging support
SDK for Android O.S.
Sample code for SDK
Digitax Framework (Digitax Libraries): GPS, Odometer, Hardware Keys, WatchDog, OTA, Stealth Mode Controller, Logs, And Restore, Light Dimmer, Hardware Identification, Alarm, Card Reader and Windows Status
Serial port driver and test tools
Digital I/O driver



## System diagnostic tools

On Field Test (OFT) OnBoard Diagnostic Utilities included, with Customizable CheckList to make tests of GPS Fix, GPS Antenna, GPRS Connectivity and Base Station Signal Quality, Odometer, Ignition, Panic Button, TouchScreen calibration, Hardware Keys, Ambient Light Sensor, Device version, OS Version, AITP Version, UPS and Battery Status, Roof Light, Navigation Software

All On Field Tests and enrolling features can be used during first installation and swap of devices.

## OS Image Loader

Over The Air (OTA) OS image loader or microSDHC Card Image Loader

## System Update Fleet Management

Professional OTA (Over The Air) CLIENT allows the update of the whole Operating System and all the CPUs Firmware (option).

Professional OTA (Over The Air) SERVER with vehicles enrolling, group management and selective update, remote debugging and logging. Web based user interface (option)

## Power Supply

8 - 32 V with Surge Protector

## Battery

Internal Battery Package (option)

## Mounting

All the External Connectors, Accessible slots (such as SIM Card, Micro SDHC, USB, etc.) and Screws are Mechanically Sealed

## Operating Temperature

-20°C to 75°C

## Humidity

Humidity up to 95% non-condensing.

## Vibration

Vibration Sine wave, 10 ~ 500 ~ 10Hz, 1.5G, 0.37oct/min 3 axis, 1hour/axis.

## Dust Ingress Protection

All connectors covers sealed, no open holes

## Dimension

204 mm x 120 mm x 35 mm (WxHxD)

## Weight

545 g



System on Chip Module



Cat.6 LTE Module



WLAN 2.4G, 802.11b/g/n  
BT 2.1 + EDR/3.0/4.1 LE



GLONASS/GPS/BeiDou



USB Interface



Powerful Multimedia Function



Android 9.x



Dedicated CPU for Automotive Intensive Task Processor



DIGITAX SDK



CAN BUS Interface



- All in One
- Automotive compliance fully certificate
- Extended Temperature Range
- Extended and filtered power supply system.
- Wide range of external interfaces
- Safe and inviolable tamper proof
- Mechanical keyboard for hot switch
- Wide range of software API for specific Hardware and
- easy user application.
- Extended 10 years supports parts and maintenance program.







**Digitax Italy Headquarter**

Via dell'Industria 16 - 62017 Porto Recanati (MC) - ITALY

Phone +39 071 7590984 r.a. - Fax +39 071 9797405 / E-mail [info@digitax.com](mailto:info@digitax.com) - Web [www.digitax.com](http://www.digitax.com)

**Digitax España**  
 C/Tomás Bretón, 7  
 28045 – Madrid  
 SPAIN  
 Phone +34 902366292  
 Fax +34 915271562  
 Web: [www.digitax-es.com](http://www.digitax-es.com)  
 E-mail: [info@digitax-es.com](mailto:info@digitax-es.com)

**Digitax Electronics U.K.**  
 Smokehouse, 31  
 Tanners Bank North Shields  
 Tyne & Wear NE 30 1 JH  
 ENGLAND  
 Phone +44 (0191) 296 1294  
 Fax +44 (0191) 257 8438  
 Web: [www.digitax.net](http://www.digitax.net)  
 E-mail: [digitaxuk@aol.com](mailto:digitaxuk@aol.com)

**Digitax Deutschland**  
 Taxitech Handelsges. mbh  
 Sommerkamp 31a - 22335  
 Hamburg  
 GERMANY  
 Phone +49 40 555 05540  
 Fax +49 40 555 05530  
 Web: [www.digitax-de.com](http://www.digitax-de.com)  
 E-mail: [digitax@taxitech.de](mailto:digitax@taxitech.de)

**Digitax Nederland B.V.**  
 Postbus 84112  
 3009 CC ROTTERDAM  
 HOLLAND  
 Phone +31 10 4512121  
 Fax : +31 10 4500453  
 E-mail: [h.wittenberg@planet.nl](mailto:h.wittenberg@planet.nl)  
 E-mail: [info@digitax.nu](mailto:info@digitax.nu)

**Digitax CO. Mauritius**  
 P.O. box 775  
 Bel Village  
 MAURITIUS  
 Phone +230 234 4533/4936  
 Fax +230 234 5866  
 Web: [www.mtl-co.net](http://www.mtl-co.net)  
 E-mail: [mtlts@intnet.mu](mailto:mtlts@intnet.mu)